

PANEL LIGHT

PRESTIGE

LED ENERGY SAVING LUMINAIRES



LED SURFACE PANEL LIGHT

15W

LUMEN
1300

20W

LUMEN
1800

DESCPRITION	CCT (K)
PLS-615R	3000K
PLS-615R	4000K
PLS-615R	6500K

SIZE
φ175mm x 35mm

DESCPRITION	CCT (K)
PLS-820R	3000K
PLS-820R	4000K
PLS-820R	6500K

SIZE
φ225mm x 35mm

26W

LUMEN
2340

DESCPRITION	CCT (K)
PLS-1226R	3000K
PLS-1226R	4000K
PLS-1226R	6500K

SIZE
φ289mm x 38mm

PRODUCT FEATURES

- Short start up time
- Adopt constant current
- Extra Bright



VOLTAGE 185-265V | **CRI** 80 | **LIFETIME** 15,000 HRS



instant
brightness



non
dimmable



15,000
hrs+



no blue light
hazard



SIRIM

PANEL LIGHT

PRESTIGE

LED ENERGY SAVING LUMINAIRES



LED SURFACE PANEL LIGHT

15W

LUMEN
1300

20W

LUMEN
1800

DESCPRITION	CCT (K)
PLS-615SQ	3000K
PLS-615SQ	4000K
PLS-615SQ	6500K

SIZE
175 x 175 x 35mm

DESCPRITION	CCT (K)
PLS-820SQ	3000K
PLS-820SQ	4000K
PLS-820SQ	6500K

SIZE
225 x 225 x 35mm

26W

LUMEN
2340

DESCPRITION	CCT (K)
PLS-1226SQ	3000K
PLS-1226SQ	4000K
PLS-1226SQ	6500K

SIZE
289 x 289 x 38mm

PRODUCT FEATURES

- Short start up time
- Adopt constant current
- Extra Bright



VOLTAGE 185-265V | **CRI** 80 | **LIFETIME** 15,000 HRS



instant
brightness



non
dimmable



15,000
hrs+



no blue light
hazard



SIRIM