



PRODUCT CATALOGUE 2018

VENTILATION FAN

EX-20SHC_{5T} (8 inch)

EX-25SHC_{5T} (10 inch)

EX-30SHC_{5T} (12 inch)

For shop, working room, living room
& kitchen

- Specially designed with oil-catcher
- Exhaust Type
- Operates Quietly
- Energy Efficient
- Easy to Clean

*NEW with extra fans
for stronger air flow*



WALL MOUNTED TYPE

EX-20SKC_{5T} (8 inch)

EX-25SKC_{5T} (10 inch)

For shop, office room, living room
& kitchen

- Exhaust Type
- Operates Quietly
- Energy Efficient
- Easy Installation
- Easy to Clean

*NEW with extra fans
for stronger air flow*



WALL MOUNTED TYPE

V-15SL_{3T} (6 inch)

V-20SL_{3T} (8 inch)

For shop, working room, living room
& kitchen

- Size: 6 inch / 8 inch
- Exhaust Type
- Operates Quietly
- Energy Efficient
- Easy to Clean



GLASS MOUNTED TYPE

**Extra
winglet
Fan**



EX-15SC_T (6 inch)

EX-20SC_{ST} (8 inch)

EX-25SC_{ST} (10 inch)

For shop, working room,
living room & kitchen

- Exhaust type
- Operates quietly
- Energy efficient
- Easy to clean



*NEW with extra fans
for stronger air flow*



CEILING MOUNTED TYPE



EX-20SSC_T (8 inch)

EX-25SSC_T (10 inch)

For shop, office room, living room
& kitchen

- Pressure-type with centrifugal fan.
- Equipped with back-draft shutter.
- Snap-fit grille.
- Quick connect terminal.
- Slide-type installation and removal.



LOW NOISE CEILING MOUNTED TYPE



Premium Safety Standard

Enhanced product safety through the use of non-self-flammable materials & concealed motor, which prevents undesirable materials from entering the motor & minimizes the possibility of accidents.

VD-10Z_{4T6}

VD-15Z_{4T6}

VD-15ZP_{4T6}

For shop, office room, living room
& kitchen

- Pressure-type with centrifugal fan.
- Humidity-resistant plastic grille.
- Equipped with back-draft shutter.
- Snap-fit grille.
- Quick connect terminal.
- Slide-type installation and removal.



DUCT CEILING MOUNTED TYPE

* VD-10Z_{4T6}-D, VD-15Z_{4T6}-D, DVD-15ZP_{4T6}-D with Delay Timer

VD-18Z_{4T5}

VD-20Z_{4T5}

VD-23Z_{4T5}

For shop, office room, living room
& kitchen

- Pressure-type with centrifugal fan.
- Equipped with back-draft shutter.
- Snap-fit grille.
- Quick connect terminal.
- Slide-type installation and removal.



DUCT CEILING MOUNTED TYPE

* VD-20Z_{4T5}, VD-23Z_{4T5} with 2 speed (High & Low) ventilation



NON SELF-FLAMMABLE

Non Self-Flammable Materials

The motor, capacitor, lead wire, cord plug, 3-pin plug, closed end as well as the printed circuit board (PCB) are made from materials with improved fire resistance.



CURRENT FUSE



THERMAL FUSE

Double Fuse Protection

Every ventilator is equipped with two fuses to meet the 100% Mitsubishi Safety Policy. The current fuse prevents the ventilator from operating when power is exceeded, while the thermal fuse cuts off power supply when the motor overheats.

CEILING FAN

Dark Grey

Light Gray



C56-RW5-P SYGY

56 inch 5 Blades Ceiling Fan

- Remote Control
- 5 Speed Level Control
- OFF Timer (1 - 3 - 6 Hrs.)
- Sleep Mode
- Rhythm Mode (Natural Wind)

Yuga 優雅

Dark Grey

Light Gray



C56-RW4-P CYGY

56 inch 5 Blades Ceiling Fan

- Remote Control
- 5 Speed Level Control
- OFF Timer (1 - 3 - 6 Hrs.)
- Sleep Mode
- Rhythm Mode (Natural Wind)

Yuga 優雅



C60-GY-P

56 / 60 inch 3 Blades Ceiling Fan

- Regulator type
- 4 speed control
- Reliable motor & low power consumption



C56-RQ5-P

56 inch 5 Blades Ceiling Fan

- ON/OFF switch remote controller
- 3-speed control with Indicator
- 1,2,4,8 hour OFF timer



C56-RQ4-P

56 inch 4 Blades Ceiling Fan

- ON/OFF switch remote controller
- 3-speed control with Indicator
- 1,2,4,8 hour OFF timer

WALL FAN



Classy Grey



White



W16-GU-P

W18-GU-P

16 / 18 inch propeller

- Designed for easy installation in small areas
- Controlled by two strings
- Reliable motor & low power consumption
- 3-speed & oscillation pull speed



Classy Grey



White



W16-RU-P

W18-RU-P

16 / 18 inch propeller

- Rhythm mode imitates natural airflow
- 3-speed Micom switch
- Automatic On-Off timer
- Reliable motor & low power consumption



Desk FAN

Classy Grey



D12-GU-P

D16-GU-P

16 inch propeller

- Oscillation angle: 80°
- Detachable base for easy storage
- Low noise level
- Reliable motor & low power consumption
- 3-speed push button switch



TATAMI FAN

Classy Grey



R16-GU-P

R18-GU-P

16 inch propeller

- With Crystal Blade
- Adjustable for large room use
- Adjustable for personal desk fan use
- Reliable motor & low power consumption
- Suitable for modern lifestyle



LIVING FAN



LV16-RU-P

LV16-GU-P

- With Crystal Blade
- Rhythm mode imitates natural airflow
- 3-speed Micom switch
- Automatic On-Off timer
- Reliable motor & low power consumption
- Extra large propeller to reduce air friction
- Super quiet operation



Cycle Fan



CY16-ST-P

CY18-SU-P

- 16 / 18 inch propeller
- Even air flow distribution throughout the room
- Oscillation angle: 360°
- Features a rotor switch capable of blocking the swinging function of the propellers



SPECIFICATIONS

MODEL	RATED VOLTAGE (V)	FREQUENCY (Hz)	POWER CONSUMPTION (W)		RPM	AIRFLOW RATE		NOISE (dB)	WEIGHT (kg)
						m ³ /h	CFM		
EX-20SHC5T	230-240	50	17-19		1300-1330	550-560	324-330	37	2.2
EX-25SHC5T	230-240	50	25-26		1130-1160	930-940	547-553	38-39	2.7
EX-30SHC5T	230-240	50	31-33		850-930	1180-1240	695-730	36-38	3.2
EX-20SKC5T	230-240	50	17-19		1300-1320	540-550	318-324	39-40	2.3
EX-25SKC5T	230-240	50	25-26		1030-1080	820-860	483-506	39-40	2.7
V-15SL6T	220-240	50	8.0-9.4		1550-1740	230-250	135-147	39-41	1.1
V-20SL6T	220-240	50	13-16		1280-1350	390-420	230-247	39-41	1.2
EX-15SCt	220-240	50	14-16		1500-1600	210-230	124-135	36-38	1.2
EX-20SC5T	230-240	50	17-19		1320-1340	470-480	277-283	41	1.8
EX-25SC5T	230-240	50	22-23		920-980	640-680	377-400	38-40	2.2
EX-20SSCt	230-240	50	18-20		1300	480	283	41	2.5
EX-25SSCt	230-240	50	24.5-25.5		1020	690-720	406-424	40.5-41.5	2.8
VD-10Z4T6	220-240	50	9-11		900-980	100-110	59-65	29-32	2.2
VD-15Z4T6	220-240	50	12-14		670-750	157-182	92-107	28-32	3.4
VD-15ZP4T6	220-240	50	17-20		870-950	217-240	128-141	35-38.5	3.4
VD-18Z4T5	220-240	50	31-37		600-650	335-365	197-215	35-39	5.8
VD-20Z4T3	220-240	50	42-50		700-760	430-460	253-271	39-42	6.5
VD-20ZP4T5	220-240	50	High	53-62	840-890	510-550	300-324	43-46	7.4
			Low	37-42	610-670	370-420	218-247	37-39	
VD-23Z4T5	220-240	50	High	75-87	650-720	580-630	341-371	46-48	8.6
			Low	37-43	440-480	360-390	212-230	35-37	
VD-23ZP4T5	220-240	50	High	95-107	930-980	715-770	421-453	48-50	9.7
			Low	59-67	600-660	450-490	265-288	39-41	
C56-RW5-P	220-240	50	65-76		190-200	≥12000	≥7063	≤60	8.2
C56-RW4-P	220-240	50	64-74		210-220	≥12000	≥7063	≤60	7.9
C56-RQ5-P	230-240	50	62.2-67.5		220-240	≥13800	≥8122	≤56	9.0
C56-RQ4-P	230-240	50	60.2-64.5		240-260	≥13800	≥8122	≤56	8.2
C60-GY-P	220-240	50	54-63		230-250	≥12000	≥7063	≤60	7.6
W16-GU-P	230-240	50	54-58		1180-1220	≥3300	≥1942	≤52	4.6
W16-RU-P	230-240	50	54-58		1180-1220	≥3300	≥1942	≤52	4.6
W18-GU-P	230-240	50	63-67		1100-1140	≥4500	≥2649	≤55	5.0
W18-RU-P	230-240	50	63-67		1100-1140	≥4500	≥2649	≤55	5.0
D16-GU-P	230-240	50	52-55		1180-1220	≥3300	≥1942	≤52	4.3
R16-GU-P	230-240	50	52-55		1180-1220	≥3300	≥1942	≤52	5.7
R18-GU-P	230-240	50	61-65		1050-1080	≥4500	≥2649	≤55	6.8
LV16-GU-P	230-240	50	52-55		1180-1220	≥3300	≥1942	≤52	7.4
LV16-RU-P	230-240	50	54-58		1180-1220	≥3300	≥1942	≤52	7.4
CY16-ST-P	230-240	50	55-58		1160-1200	≥3300	≥1942	≤52	4.8
CY18-SU-P	230-240	50	61-65		1150-1190	≥4500	≥2649	≤55	4.9

MESM-VF2-19



HEAD OFFICE:
MITSUBISHI ELECTRIC SALES MALAYSIA SDN BHD (11098-W)

Lot 11, Jalan 219, PO Box 1036, 46860 Petaling Jaya,
Selangor Darul Ehsan, Malaysia.

Tel: 03-7955 2088 Fax: 03-7958 2576

Service Hotline: 03-7955 3097

Website: www.mitsubishielectricmalaysia.com



Search & Download "MESM" apps

