

**Panasonic**

INTELLIGENT ECO SENSORS

**ECONAVI**

**LED**

**DC Motor**  
ENERGY SAVING

## Fan

Ceiling  
General  
Ventilation



**BREEZE for LIVING SPACE**

**Panasonic**

Please visit **Panasonic Fan Microsite** for more details:  
[www.panasonic.com.my/fan](http://www.panasonic.com.my/fan)

- All information contained in this catalogue is correct at the time of printing, and is subject to change without prior notice.
- Images are for illustration purpose only.
- Due to printing considerations, the actual color may vary slightly from those shown.
- Panasonic Malaysia Sdn. Bhd. reserves the right to revise any content in this catalogue as it deems fit without prior notice.

Panasonic Malaysia Sdn Bhd (26975-W)  
Customer Care Centre: Tel: 03-7953 7600 (Mon to Fri: 9am-5pm)  
Lot 10, Jalan 13/2, 46200 Petaling Jaya, Selangor Darul Ehsan.  
Email: [ccc@my.panasonic.com](mailto:ccc@my.panasonic.com) [www.panasonic.com.my](http://www.panasonic.com.my)

## Oscillation Fan F-MQ409 / F-MQ409 DG

### Features

- Thermal Safety Fuse
- Regulator 5-speed Selection
- Transparent Plastic Blades
- 360° Oscillation Circle
- Durable Condenser Motor
- Adjustment Angle - 15°, 30° And 50°

### Blade Size

Width: 40cm [16"]

### Colour

White / Dark Grey



F-MQ409 DG

F-MQ409

## Wall Fan F-MU44R

### Features

- Full Multi-functional Remote Control With On/Off Function, 3-speed Control, Timer Setting And Oscillation Control
- 1,3,6-Hour Timer
- Ball-bearing Motor
- Thermal Safety Fuse

### Blade Size

Width: 40cm [16"]

### Colour

White



F-MU44R

## Wall Fan F-MU453

### Features

- 3-speed On/Off Pull Switch
- Oscillation Control By Pull Switch
- Durable Condenser Motor With Permanently Lubricated Ball-bearing Assembly
- Transparent Plastic Blades
- Thermal Safety Fuse

### Blade Size

Width: 45cm [18"]

### Colour

Dark Grey



F-MU453

## Wall Fan F-MU405

### Features

- 5-blade design for Better Air Delivery
- 3-speed On/Off Pull Switch
- Oscillation Control By Pull Switch
- Durable Condenser Motor With Permanently Lubricated Ball-bearing Assembly
- Transparent Plastic Blades
- Thermal Safety Fuse

### Blade Size

Width: 40cm [16"]

### Colour

Dark Grey



**New Design- Slim & Sleek**  
with slimmer guard depth of 130mm that is space saving



Slim design

**New 5 Blade Design Technology**  
for a wider airflow performance



Normal Wall Fan  
928 mm

F-MU405  
940 mm

Airflow surrounding for normal wall fan and F-MU405

**Silent Operation**  
low noise with 52dB



## Wall Fan F-MU408 / F-MU308

### Features

- 3-blade design for Better Air Delivery
- 3-speed On/Off Pull Switch
- Oscillation Control By Pull Switch
- Durable Condenser Motor With Permanently Lubricated Ball-bearing Assembly
- Transparent Plastic Blades
- Thermal Safety Fuse

### Blade Size

40cm [16"] - F-MU408  
30cm [12"] - F-MU308

### Colour

White













F-MU408



F-MU308



# Products Line-Up

SERIES	TABLE FAN		STAND FAN		OSCILLATION FAN	WALL FAN				
General Fan										
	F-MN404	F-MN304	F-MT405	F-MX405	F-MQ409 / F-MQ409 DG	F-MU44R	F-MU453	F-MU405	F-MU408	F-MU308
<b>FEATURES</b>										
Size	40cm (16")	30cm (12")	40cm (16")	40cm (16")	40cm (16")	40cm (16")	45cm (18")	40cm (16")	40cm (16")	30cm (12")

SERIES	WALL MOUNT		WALL MOUNT (INDUSTRIAL)		GLASS MOUNT	CEILING MOUNT		CEILING MOUNT SIROCCO		
Ventilation Fan										
	FV-25AUF1	FV-10EGK1 / FV-15EGK1	FV-20AUM8 / FV-25AUM7 / FV-30AUM8	FV-20AL9 / FV-25AL9	FV-40KUTP	FV-15WU4 / FV-20WU4	FV-25TGU3	FV-20CUT1P	FV-17CLM XVBSH / FV-17CLM XVBHH	FV-24CLM XVBSH / FV-24CLM XVBHH
<b>FEATURES</b>										
Size	25cm (10")	10cm (4") / 15cm (6")	20cm (8") / 25cm (10") / 30cm (12")	20cm (8") / 25cm (10")	40cm (16")	15cm (6") / 20cm (8")	25cm (10")	20cm (8")	17cm (6.8")	24cm (9.6")

# Specification

## Ceiling Fan

SERIES	ECONAVI				LED				NAMI FAN		BAYU 5 FAN		BAYU 4 FAN	BAYU 3 FAN	BAYU JR FAN	REGULATOR FAN		
MODEL	50Hz		F-M15H5	F-M14HW	F-M15GW	F-M12GX VBHQH	F-M15E2	F-M14E2	F-M14D5 DG/VBPH/WT		F-M14C5 DG/VBPH/WT	F-M14C2	F-M12D2	F-M15A0/GY	F-M15B0	F-M12A0		
Power Consumption	Low	W	3	2.5	25	21	21	20	21		20	34	21	17	17	18		
	High	W	41	41	63	46	85	85	69		68	65	85	72	72	51		
Fan Speed	Low	RPM	80	81	80	80	84	102	95		102	113	205	103	103	154		
	High	RPM	235	239	235	236	195	215	183		196	257	250	240	240	303		
Air Velocity	m/min		210	185	210	185	195	180	170		170	159	185	165	165	169		
Air Delivery	m <sup>3</sup> /min		245	225	245	187	225	225	215		215	210	187	230	230	162		

## General Fan

SERIES	STAND FAN (WITH TIMER)		STAND FAN		TABLE FAN				OSCILLATION FAN		WALL FAN (WITH REMOTE CONTROL)		WALL FAN		
MODEL	50Hz		F-MT405	F-MX405	F-MN404	F-MN304		F-MQ409	F-MQ409 DG	F-MU44R		F-MU453	F-MU408	F-MU308	F-MU405
Power Consumption	Low	W	45	45	45	28		20	20	45		46	45	28	43
	High	W	58	58	58	39		52	52	59		60	54	38	54
Fan Speed	Low	RPM	850	850	850	976		631	631	891		850	891	945	966
	High	RPM	1,210	1,210	1,210	1,248		1,178	1,178	1,175		1,085	1,175	1,228	1,210
Air Velocity	m/min		250	250	250	214		278	278	251		258	258	214	192
Air Delivery	m <sup>3</sup> /min		84.6	84.6	84.6	43		85	85	85		85	85	43	80

## Ventilation Fan

SERIES	WALL MOUNT																(INDUSTRIAL)				GLASS MOUNT				CEILING MOUNT				CEILING MOUNT SIROCCO							
MODEL	50Hz		FV-25AUF1		FV-10EGK1		FV-15EGK1		FV-20AUM8		FV-25AUM7		FV-30AUM8		FV-20AL9		FV-25AL9		FV-40KUTP		FV-15WU4		FV-20WU4		FV-25TGU3		FV-20CUT1P		FV-17CLM XVBSh		FV-17CLM XVBHh		FV-24CLM XVBSh		FV-24CLM XVBHh	
Air Volume	cfm	cmh	491	835	45	75	96	165	318	540	530	900	727	1,235	322	545	493	835	1,243	2,115	124	210	212	360	367	625	265	450	53	90	53	90	94	160	94	160
Motor	W		34		6		7		17		29		33		22		29		68		8		16		24		26		13		13		17		17	
Fan Speed	RPM		1,100		2,732		2,405		1,205		1,110		980		1,210		1,055		1,220		1,463		1,042		1,010		1,207		860		860		795		795	
Weight	kg		2.8		1.2		1.5		2.3		2.6		3.0		2.2		2.7		6.4		0.9		1.1		1.9		1.8		2.0		2.0		3.2		3.2	
Low Noise Level	dB		42		33		35		37		39		45		40		43		51		35		32		45		41		29		29		31		31	
Low Electricity Consumption 24 Hours	RM		0.18		0.03		0.04		0.09		0.15		0.17		0.12		0.15		0.36		0.04		0.08		0.13		0.14		0.07		0.07		0.09		0.09	